2014 Super Duty F-Series Trucks
Order Guide Supplemental Reference

8/14/13

This supplement contains Maximum Payload Charts, Snow Plow Application Charts, Cab-to-Axle dimensions and Spring Selection Charts.

This information will help you in selecting the right truck to meet your customers' needs.

Please refer to the appropriate 2014 Source Book section for more complete weight rating information.

CONTENTS

Payload Package Selection Charts
- F-250 SRW Pickup 1
- F-350 SRW Pickup 2
- F-350 DRW Pickup 3
- F-450 DRW Pickup 4
- F-350 SRW Chassis Cab 5
- F-350 DRW Chassis Cab 6
- F-450 Chassis Cab 7
- F-550 Chassis Cab 8

Snow Plow Applications Charts 9

Cab-to-Axle Dimension Chart 10

Front Spring/GAWR Selection Charts
- F-250 SRW Pickup 11
- F-350 SRW Pickup/Pickup Box Delete 12
- F-350 DRW Pickup/Pickup Box Delete 13
- F-450 DRW Pickup 14
- F-350 SRW Chassis Cab 15
- F-350 DRW Chassis Cab 16
- F-450 Chassis Cab 17
- F-550 Chassis Cab 18

2014 SUPER DUTY F-SERIES TRUCKS
MAXIMUM PAYLOAD PACKAGE SELECTOR CHARTS

F-250 Pickup

GVWR (Standard)

	Cab	Regular Cab		Super Cab				Crew Cab			
	Wheelbase	137"		141.8"		158.0"		156.2"		172.4"	
Drive	Engine	GVWR (lbs)	Max Payload (lbs)	GVWR (lbs)	Max Payload (lbs)	GVWR (lbs)	Max Payload (lbs)	GVWR (lbs)	Max Payload (lbs)	GVWR (lbs)	Max Payload (lbs)
4x2	6.2L	10,000	4,240	10,000	3,860	10,000	3,760	10,000	3,640	10,000	3,540
	6.7L	10,000	3,500	10,000	3,180	10,000	3,010	10,000	2,980	10,000	2,800
4x4	6.2L	10,000	3,780	10,000	3,450	10,000	3,350	10,000	3,250	10,000	3,140
	6.7L	10,000	3,080	10,000	2,830	10,000	2,620	10,000	2,620	10,000	2,410

GVWR (Optional)

	Cab	Regular Cab		Super Cab				Crew Cab			
	Wheelbase	137"		141.8"		158.0"		156.2"		172.4"	
Drive	Engine	GVWR (lbs)	Max Payload (lbs)	GVWR (lbs)	Max Payload (lbs)	GVWR (lbs)	Max Payload (lbs)	GVWR (lbs)	Max Payload (lbs)	GVWR (lbs)	Max Payload (lbs)
4x2	6.2L	9,900	4,130	9,900	3,760	9,900	3,660	9,900	3,540	9,900	3,440
	6.7L	9,900	3,400	9,900	3,080	9,900	2,910	9,900	2,880	9,900	2,700
4x4	6.2L	9,900	3,630	9,900	3,350	9,900	3,250	9,900	3,150	9,900	3,040
	6.7L	9,900	2,980	9,900	2,730	9,900	2,520	9,900	2,520	9,900	2,310

2014 SUPER DUTY F-SERIES TRUCKS
MAXIMUM PAYLOAD PACKAGE SELECTOR CHARTS

F-350 SRW Pickup
Standard GVWR for 17" Wheel & Tire

Cab		Regular Cab		Super Cab				Crew Cab			
Wheelbase		137.0"		141.8"		158.0"		156.2"		172.4"	
Drive	Engine	GVWR (lbs)	Max Payload (lbs)	GVWR (lbs)	Max Payload (lbs)	GVWR (lbs)	Max Payload (lbs)	GVWR (lbs)	Max Payload (lbs)	GVWR (lbs)	Max Payload (lbs)
4x2	6.2L	10,000	4,080	10,000	3,790	10,200	3,920	10,200	3,800	10,500	3,970
	6.7L	10,500	3,930	10,700	3,810	10,800	3,780	10,800	3,740	11,100	3,870
4x4	6.2L	10,400	4,060	10,500	3,900	10,700	4,010	10,600	3,810	10,800	3,900
	6.7L	10,800	3,810	11,100	3,850	11,200	3,770	11,200	3,750	11,200	3,560

Optional Fixed GVWR

Cab		Regular Cab		Super Cab				Crew Cab			
Wheelbase		137.0"		141.8"		158.0"		156.2"		172.4"	
Drive	Engine	GVWR (lbs)	Max Payload (lbs)	GVWR (lbs)	Max Payload (lbs)	GVWR (lbs)	Max Payload (lbs)	GVWR (lbs)	Max Payload (lbs)	GVWR (lbs)	Max Payload (lbs)
4x2	6.2L	10,000	4,080	10,000	3,790	10,000	3,720	10,000	3,600	10,000	3,470
	6.7L	10,000	3,430	10,000	3,110	10,000	2,980	10,000	2,940	10,000	2,770
4x4	6.2L	10,000	3,660	10,000	3,400	10,000	3,310	10,000	3,210	10,000	3,100
	6.7L	10,000	3,010	10,000	2,750	10,000	2,570	10,000	2,550	10,000	2,360

Standard Variable GVWR for 18" Wheel & Tire 4x2

Cab		Regular Cab		Super Cab				Crew Cab			
Wheelbase		137.0"		141.8"		158.0"		156.2"		172.4"	
Drive	Engine	GVWR (lbs)	Max Payload (lbs)	GVWR (lbs)	Max Payload (lbs)	GVWR (lbs)	Max Payload (lbs)	GVWR (lbs)	Max Payload (lbs)	GVWR (lbs)	Max Payload (lbs)
4x2	6.2L	10,500	4,540	10,500	4,250	10,900	4,580	10,700	4,260	11,000	4,430
	6.7L	11000	4390	11000	4070	11500	4430	11400	4300	11500	4220
	6.7L	---	---	---	---	11400	4330	---	---	11400	4120

Standard Variable GVWR for 18" Wheel & All-Season Tire 4x4

Cab		Regular Cab		Super Cab				Crew Cab			
Wheelbase		137.0"		141.8"		158.0"		156.2"		172.4"	
Drive	Engine	GVWR (lbs)	Max Payload (lbs)	GVWR (lbs)	Max Payload (lbs)	GVWR (lbs)	Max Payload (lbs)	GVWR (lbs)	Max Payload (lbs)	GVWR (lbs)	Max Payload (lbs)
4x4	6.2L	10,500	4,110	10,600	3,950	10,800	4,070	10,800	3,970	11,000	4,060
	6.7L	11,000	3,970	11,200	3,910	11,300	3,830	11,300	3,810	11,300	3,610

Standard GVWR for 18" Wheel & All-Terrain Tire (inc. 20" with Diesel) 4x4

Cab		Regular Cab		Super Cab				Crew Cab			
Wheelbase		137.0"		141.8"		158.0"		156.2"		172.4"	
Drive	Engine	GVWR (lbs)	Max Payload (lbs)	GVWR (lbs)	Max Payload (lbs)	GVWR (lbs)	Max Payload (lbs)	GVWR (lbs)	Max Payload (lbs)	GVWR (lbs)	Max Payload (lbs)
4x4	6.2L	11,300	4,930	11,100	4,420	11,000	4,240	11,300	4,440	11,200	4,220
		11,100*	4,680								
	6.7L	11,500	4,430	11,500	4,180	11,500	4,000	11,500	3,970	11,500	3,780
	6.7L	11,400	4,330	11,400	4,080	11,400	3,900	11,400	3,870	11,400	3,680

* Camper Package only

2014 SUPER DUTY F-SERIES TRUCKS

MAXIMUM PAYLOAD PACKAGE SELECTOR CHARTS

F-350 DRW Pickup (also includes Gasoline Pickup Box Delete)

Maximum GVWR

Cab		Regular Cab		Super Cab			Crew Cab		
Wheelbase		137.0"		158"				172.4"	
Drive	Engine	GVWR (lbs)	Max Payload (lbs)	GVWR (lbs)	Max Payload (lbs)			GVWR (lbs)	Max Payload (lbs)
4x2	6.2L	13,500	7,260	13,900	7,210			14,000	7,080
	6.7L	14,000	7,060	14,000	6,560			14,000	6,340
4x4	6.2L	13,800	7,090	14,000	6,890			14,000	6,670
	6.7L	14,000	6,640	14,000	6,150			14,000	5,930

F-350 DRW Pickup Box Delete (also includes Diesel Pickup Box Delete)

Maximum GVWR

Cab		Regular Cab		Super Cab			Crew Cab		
Wheelbase		137.0"		158"				172.4"	
Drive	Engine	GVWR (lbs)	Max Payload (lbs)	GVWR (lbs)	Max Payload (lbs)			GVWR (lbs)	Max Payload (lbs)
4x2	6.7L	13,000	6,660	13,000	6,160			13,000	5,930
4x4	6.7L	13,000	6,240	13,000	5,750			13,000	5,530

2014 SUPER DUTY F-SERIES TRUCKS

MAXIMUM PAYLOAD PACKAGE SELECTOR CHARTS

F-450 DRW Pickup

GVWR
(Standard)

Cab	Regular Cab		Super Cab				Crew Cab			
Wheelbase	137"		142"		158"		156"		172.4"	
Drive / Engine	GVWR (lbs)	Max Payload (lbs)	GVWR (lbs)	Max Payload (lbs)	GVWR (lbs)	Max Payload (lbs)	GVWR (lbs)	Max Payload (lbs)	GVWR (lbs)	Max Payload (lbs)
4x4 6.7L	---	---	---	---	---	---	---	---	14,000	5,880

2014 SUPER DUTY F-SERIES TRUCKS
MAXIMUM PAYLOAD PACKAGE SELECTOR CHARTS

F-350 SRW Chassis Cab
Optional Fixed 9800 GVWR

		Regular Cab								Super Cab		Crew Cab			
		60" CA		84" CA		108" CA		120" CA		60" CA		60" CA		84" CA	
Drive	Engine	GVWR (lbs)	Max Payload (lbs)	GVWR (lbs)	Max Payload (lbs)	GVWR (lbs)	Max Payload (lbs)	GVWR (lbs)	Max Payload (lbs)	GVWR (lbs)	Max Payload (lbs)	GVWR (lbs)	Max Payload (lbs)	GVWR (lbs)	Max Payload (lbs)
4x2	6.2L	9,800	4,320	---	---	---	---	---	---	9,800	4,024	9,800	3,775	---	---
	6.7L	9,800	3,617	---	---	---	---	---	---	9,800	3,267	9,800	2,933	---	---
4x4	6.2L	9,800	3,954	---	---	---	---	---	---	9,800	3,563	9,800	3,337	---	---
	6.7L	9,800	3,254	---	---	---	---	---	---	9,800	2,817	9,800	2,522	---	---

Standard GVWR for 18" Tires/Wheels/28-gallon Miship Fuel Tank

		Regular Cab								Super Cab		Crew Cab			
		60" CA		84" CA		108" CA		120" CA		60" CA		60" CA		84" CA	
Drive	Engine	GVWR (lbs)	Max Payload (lbs)	GVWR (lbs)	Max Payload (lbs)	GVWR (lbs)	Max Payload (lbs)	GVWR (lbs)	Max Payload (lbs)	GVWR (lbs)	Max Payload (lbs)	GVWR (lbs)	Max Payload (lbs)	GVWR (lbs)	Max Payload (lbs)
4x2	6.2L	10,000	4,469	---	---	---	---	---	---	10,000	4,172	10,000	3,924	---	---
	6.7L	10,000	3,766	---	---	---	---	---	---	10,000	3,415	10,000	3,082	---	---
4x4	6.2L	10,000	4,103	---	---	---	---	---	---	10,000	3,712	10,000	3,485	---	---
	6.7L	10,000	3,403	---	---	---	---	---	---	10,000	2,966	10,000	2,670	---	---

Standard/Variable GVWR for 18" Wheel & Tire - 4x2

		Regular Cab								Super Cab		Crew Cab			
		60" CA		84" CA		108" CA		120" CA		60" CA		60" CA		84" CA	
Drive	Engine	GVWR (lbs)	Max Payload (lbs)	GVWR (lbs)	Max Payload (lbs)	GVWR (lbs)	Max Payload (lbs)	GVWR (lbs)	Max Payload (lbs)	GVWR (lbs)	Max Payload (lbs)	GVWR (lbs)	Max Payload (lbs)	GVWR (lbs)	Max Payload (lbs)
4x2	6.2L	10,200	4,723	---	---	---	---	---	---	10,600	4,644	10,700	4,496	---	---
	6.7L	11,000	4,628	---	---	---	---	---	---	11,500	4,777	11,500	4,443	---	---

Standard/Variable GVWR for 18" Wheel & Tire - 4x4

		Regular Cab								Super Cab		Crew Cab			
		60" CA		84" CA		108" CA		120" CA		60" CA		60" CA		84" CA	
Drive	Engine	GVWR (lbs)	Max Payload (lbs)	GVWR (lbs)	Max Payload (lbs)	GVWR (lbs)	Max Payload (lbs)	GVWR (lbs)	Max Payload (lbs)	GVWR (lbs)	Max Payload (lbs)	GVWR (lbs)	Max Payload (lbs)	GVWR (lbs)	Max Payload (lbs)
4x4	6.2L	10,200	4,175	---	---	---	---	---	---	10,600	4,184	10,700	4,057	---	---
	6.7L	11,100	4,365	---	---	---	---	---	---	11,500	4,328	11,500	4,032	---	---

2014 SUPER DUTY F-SERIES TRUCKS

MAXIMUM PAYLOAD PACKAGE SELECTOR CHARTS

F-350 DRW

Standard Fixed GVWR

		Regular Cab				Super Cab		Crew Cab	
		60" CA		84" CA		60" CA		60" CA	
Drive	Engine	GVWR (lbs)	Max Payload (lbs)	GVWR (lbs)	Max Payload (lbs)	GVWR (lbs)	Max Payload (lbs)	GVWR (lbs)	Max Payload (lbs)
4x2	6.2L	13,700	7,872	14,000	7,872	14,000	7,619	14,000	7,361
	6.7L	14,000	7,226	14,000	7,135	14,000	6,864	14,000	6,627
4x4	6.2L	14,000	7,541	14,000	7,440	14,000	7,126	14,000	6,932
	6.7L	14,000	6,801	14,000	6,705	14,000	6,409	14,000	6,205

2014 SUPER DUTY F-SERIES TRUCKS
MAXIMUM PAYLOAD PACKAGE SELECTOR CHARTS

F-450

Standard Fixed 16,500 GVWR

		Regular Cab								Super Cab				Crew Cab			
		60" CA		84" CA		108" CA		120" CA		60" CA		84" CA		60" CA		84" CA	
Drive	Engine	GVWR (lbs)	Payload (lbs)	GVWR (lbs)	Payload (lbs)	GVWR (lbs)	Payload (lbs)	GVWR (lbs)	Payload (lbs)	GVWR (lbs)	Payload (lbs)	GVWR (lbs)	Payload (lbs)	GVWR (lbs)	Payload (lbs)	GVWR (lbs)	Payload (lbs)
4x2	6.8L	16,500	9,945	16,500	9,815	16,500	9,575	16,500	9,486	16,500	9,523	16,500	9,269	16,500	9,325	16,500	9,197
	6.7L	16,500	9,219	16,500	9,038	16,500	8,757	16,500	8,655	16,500	8,727	16,500	8,516	16,500	8,519	16,500	8,369
4x4	6.8L	16,500	9,651	16,500	9,495	16,500	9,223	16,500	9,188	16,500	9,194	16,500	8,991	16,500	8,977	16,500	8,846
	6.7L	16,500	8,888	16,500	8,688	16,500	8,440	16,500	8,316	16,500	8,358	16,500	8,177	16,500	8,153	16,500	8,030

Optional Fixed 15,000 GVWR

		Regular Cab								Super Cab				Crew Cab			
		60" CA		84" CA		108" CA		120" CA		60" CA		84" CA		60" CA		84" CA	
Drive	Engine	GVWR (lbs)	Max Payload (lbs)	GVWR (lbs)	Max Payload (lbs)	GVWR (lbs)	Max Payload (lbs)	GVWR (lbs)	Max Payload (lbs)	GVWR (lbs)	Max Payload (lbs)	GVWR (lbs)	Max Payload (lbs)	GVWR (lbs)	Max Payload (lbs)	GVWR (lbs)	Max Payload (lbs)
4x2	6.8L	15,000	8,445	15,000	8,315	15,000	8,075	15,000	7,986	15,000	8,023	15,000	7,769	15,000	7,825	15,000	7,697
	6.7L	15,000	7,719	15,000	7,538	15,000	7,257	15,000	7,155	15,000	7,227	15,000	7,016	15,000	7,019	15,000	6,869
4x4	6.8L	15,000	8,151	15,000	7,995	15,000	7,723	15,000	7,688	15,000	7,694	15,000	7,491	15,000	7,477	15,000	7,346
	6.7L	15,000	7,388	15,000	7,188	15,000	6,940	15,000	6,816	15,000	6,858	15,000	6,677	15,000	6,653	15,000	6,530

Optional Fixed 16,000 GVWR

		Regular Cab								Super Cab				Crew Cab			
		60" CA		84" CA		108" CA		120" CA		60" CA		84" CA		60" CA		84" CA	
Drive	Engine	GVWR (lbs)	Max Payload (lbs)	GVWR (lbs)	Max Payload (lbs)	GVWR (lbs)	Max Payload (lbs)	GVWR (lbs)	Max Payload (lbs)	GVWR (lbs)	Max Payload (lbs)	GVWR (lbs)	Max Payload (lbs)	GVWR (lbs)	Max Payload (lbs)	GVWR (lbs)	Max Payload (lbs)
4x2	6.8L	16,000	9,445	16,000	9,315	16,000	9,075	16,000	8,986	16,000	9,023	16,000	8,769	16,000	8,825	16,000	8,697
	6.7L	16,000	8,719	16,000	8,538	16,000	8,257	16,000	8,155	16,000	8,227	16,000	8,016	16,000	8,019	16,000	7,869
4x4	6.8L	16,000	9,151	16,000	8,995	16,000	8,723	16,000	8,688	16,000	8,694	16,000	8,491	16,000	8,477	16,000	8,346
	6.7L	16,000	8,388	16,000	8,188	16,000	7,940	16,000	7,816	16,000	7,858	16,000	7,677	16,000	7,653	16,000	7,530

2014 SUPER DUTY F-SERIES TRUCKS
MAXIMUM PAYLOAD PACKAGE SELECTOR CHARTS

F-550

Standard 18,000 GVWR

		Regular Cab								Super Cab				Crew Cab			
		60" CA		84" CA		108" CA		120" CA		60" CA		84" CA		60" CA		84" CA	
Drive	Engine	GVWR (lbs)	Max Payload (lbs)	GVWR (lbs)	Max Payload (lbs)	GVWR (lbs)	Max Payload (lbs)	GVWR (lbs)	Max Payload (lbs)	GVWR (lbs)	Max Payload (lbs)	GVWR (lbs)	Max Payload (lbs)	GVWR (lbs)	Max Payload (lbs)	GVWR (lbs)	Max Payload (lbs)
4x2	6.8L	18,000	11,445	18,000	11,315	18,000	11,075	18,000	10,986	18,000	11,023	18,000	10,769	18,000	10,825	18,000	10,697
	6.7L	18,000	10,719	18,000	10,538	18,000	10,257	18,000	10,155	18,000	10,227	18,000	10,016	18,000	10,019	18,000	9,869
4x4	6.8L	18,000	11,151	18,000	10,995	18,000	10,723	18,000	10,688	18,000	10,694	18,000	10,491	18,000	10,477	18,000	10,346
	6.7L	18,000	10,388	18,000	10,188	18,000	9,940	18,000	9,816	18,000	9,858	18,000	9,677	18,000	9,653	18,000	9,530

Optional 17,500 GVWR

		Regular Cab								Super Cab				Crew Cab			
		60" CA		84" CA		108" CA		120" CA		60" CA		84" CA		60" CA		84" CA	
Drive	Engine	GVWR (lbs)	Max Payload (lbs)	GVWR (lbs)	Max Payload (lbs)	GVWR (lbs)	Max Payload (lbs)	GVWR (lbs)	Max Payload (lbs)	GVWR (lbs)	Max Payload (lbs)	GVWR (lbs)	Max Payload (lbs)	GVWR (lbs)	Max Payload (lbs)	GVWR (lbs)	Max Payload (lbs)
4x2	6.8L	17,500	10,945	17,500	10,815	17,500	10,575	17,500	10,486	17,500	10,523	17,500	10,269	17,500	10,325	17,500	10,197
	6.7L	17,500	10,219	17,500	10,038	17,500	9,757	17,500	9,655	17,500	9,727	17,500	9,516	17,500	9,519	17,500	9,369
4x4	6.8L	17,500	10,651	17,500	10,495	17,500	10,223	17,500	10,188	17,500	10,194	17,500	9,991	17,500	9,977	17,500	9,846
	6.7L	17,500	9,888	17,500	9,688	17,500	9,440	17,500	9,316	17,500	9,358	17,500	9,177	17,500	9,153	17,500	9,030

Optional 19,000 GVWR

		Regular Cab								Super Cab				Crew Cab			
		60" CA		84" CA		108" CA		120" CA		60" CA		84" CA		60" CA		84" CA	
Drive	Engine	GVWR (lbs)	Max Payload (lbs)	GVWR (lbs)	Max Payload (lbs)	GVWR (lbs)	Max Payload (lbs)	GVWR (lbs)	Max Payload (lbs)	GVWR (lbs)	Max Payload (lbs)	GVWR (lbs)	Max Payload (lbs)	GVWR (lbs)	Max Payload (lbs)	GVWR (lbs)	Max Payload (lbs)
4x2	6.8L	19,000	12,300														
4x4	6.8L	19,000	11,973														

Optional 19,500 GVWR

		Regular Cab								Super Cab				Crew Cab			
		60" CA		84" CA		108" CA		120" CA		60" CA		84" CA		60" CA		84" CA	
Drive	Engine	GVWR (lbs)	Max Payload (lbs)	GVWR (lbs)	Max Payload (lbs)	GVWR (lbs)	Max Payload (lbs)	GVWR (lbs)	Max Payload (lbs)	GVWR (lbs)	Max Payload (lbs)	GVWR (lbs)	Max Payload (lbs)	GVWR (lbs)	Max Payload (lbs)	GVWR (lbs)	Max Payload (lbs)
4x2	6.8L			19,500	12,660	19,500	12,471	19,500	12,410	19,500	12,382	19,500	12,214	19,500	12,250	19,500	12,015
	6.7L	19,500	12,024	19,500	11,843	19,500	11,674	19,500	11,660	19,500	11,559	19,500	11,439	19,500	11,351	19,500	11,212
4x4	6.8L			19,500	12,321	19,500	12,150	19,500	12,049	19,500	12,012	19,500	11,924	19,500	11,800	19,500	11,691
	6.7L	19,500	11,714	19,500	11,529	19,500	11,348	19,500	11,299	19,500	11,240	19,500	11,107	19,500	10,998	19,500	10,882

2014 SUPER DUTY F-SERIES TRUCKS

SNOW PLOW APPLICATION CHARTS

F-250-450 4x4 Pickup/Box Delete Models (with Driver and One Passenger)

Cab Style	Wheelbase	Engine	F-250 * 4x4 (17")	F-350 SRW 4x4 (18")*	F-350 DRW 4x4	F-450 4x4
Regular Cab	137.0"	6.2L V-8	100/1005	100/1005	100/1005	N/R
		6.7L V-8 Dsl	100/1005	100/1005	100/1005	N/R
SuperCab	141.8"	6.2L V-8	100/1005	100/1005	N/R	N/R
		6.7L V-8 Dsl	100/950	100/950	N/R	N/R
	158.0"	6.2L V-8	100/1005	100/1005	100/1005	N/R
		6.7L V-8 Dsl	100/800	100/850	100/800	N/R
Crew Cab	156.2"	6.2L V-8	100/1005	100/1005	N/R	N/R
		6.7L V-8 Dsl	100/800	100/850	N/R	N/R
	172.4"	6.2L V-8	100/1005	100/1005	100/1005	N/R
		6.7L V-8 Dsl	100/750	100/750	100/650	100/650

Legend: * Considering max. GAWR and A/T tires. 100/750= Maximum 100 lbs. of permanently attached hardware/maximum 750 lbs. of removable plow blade and hardware. The plow and hardware weight limits are shown based upon a vehicle with 33% EPA option content and 300 lbs for the driver and front-seat passenger (150 lbs each). This chart ONLY shows Maximum recommended values.

N/R = Not recommended for snow plow application. Snow Plow Package not available.

F-350 4x4 and F-450/F-550 4x2/4x4 Chassis Cab Models (with Driver and One Passenger)

Cab Style	Wheelbase/ CA	Engine	F-350 SRW 4x4	F-350 DRW 4x4 14,000-lb. GVWR	F-450 4x2 16,500-lb. GVWR	F-450 4x4 16,500-lb. GVWR	F-550 4x2 18,000-lb. GVWR	F-550 4x4 18,000-lb. GVWR	F-550+ 4x2 19,000/ 19,500-lb. GVWR	F-550+ 4x4 19,000/ 19,500-lb. GVWR
Regular Cab	140.8"/60"	6.2L V-8	100/1005	100/1005	X	X	X	X	X	X
		6.8LV-10	X	X	100/1350	100/1350	100/1350	100/1350	100/1350	100/1350
		6.7L V-8 Dsl	100/1005	100/950	100/1350	100/1350	100/1350	100/1350	100/1350	100/1350
	164.8"/84"	6.2L V-8	X	100/1005	X	X	X	X	X	X
		6.8LV-10	X	X	100/1350	100/1350	100/1350	100/1350	100/1350	100/1350
		6.7L V-8 Dsl	X	100/900	100/1350	100/1350	100/1350	100/1350	100/1350	100/1350
	188.8"/108"	6.2L V-8	X	X	X	X	X	X	X	X
		6.8L V-10	X	X	100/1350	100/1350	100/1350	100/1350	100/1350	100/1350
		6.7L V-8 Dsl	X	X	100/1350	100/1350	100/1350	100/1350	100/1350	100/1350
	200.8"/120"	6.2L V-8	X	X	X	X	X	X	X	X
		6.8LV-10	X	X	100/1350	100/1350	100/1350	100/1350	100/1350	100/1350
		6.7L V-8 Dsl	X	X	100/1350	100/1350	100/1350	100/1300	100/1350	100/1350
Super Cab	161.8"/60"	6.2L V-8	100/1005	100/1005	X	X	X	X	X	X
		6.8LV-10	X	X	100/1350	100/1350	100/1350	100/1350	100/1350	100/1350
		6.7L V-8 Dsl	100/900	100/750	100/1350	100/1350	100/1350	100/1300	100/1350	100/1300
	185.8"/84"	6.2L V-8	X	X	X	X	X	X	X	X
		6.8LV-10	X	X	100/1350	100/1350	100/1350	100/1350	100/1350	100/1350
		6.7L V-8 Dsl	X	X	100/1350	100/1300	100/1350	100/1250	100/1350	100/1250
Crew Cab	176.2"/60"	6.2L V-8	100/1005	100/1005	X	X	X	X	X	X
		6.8LV-10	X	X	100/1350	100/1350	100/1350	100/1350	100/1350	100/1350
		6.7L V-8 Dsl	100/800	100/700	100/1350	100/1250	100/1350	100/1250	100/1350	100/1250
	200.2"/84"	6.2L V-8	X	X	X	X	X	X	X	X
		6.8LV-10	X	X	100/1350	100/1350	100/1350	100/1350	100/1350	100/1350
		6.7L V-8 Dsl	X	X	100/1350	100/1200	100/1350	100/1150	100/1350	100/1150

Legend: 100/750= Maximum 100 lbs. of permanently attached hardware. Maximum 750 lbs. of removable plow blade and hardware (maximum plow system weight is the sum of these). Th weight limits are shown based upon a vehicle with maximum buildable option content and 300 lbs for the driver and front-seat passenger (150 lbs each).

This chart ONLY shows Maximum recommended values.

X = Unavailable vehicle configuration.

2014 SUPER DUTY F-SERIES TRUCKS
CAB-TO-AXLE DIMENSION CHART

Model	Cab	Wheelbase (inches)	Cab-to-Axle (CA) (inches)	Pickup	Box Delete (1)	Chassis Cab
F-250	Reg. Cab	137	56	8' Box	Yes	--
	Super Cab	142	40	6.75' Box	--	--
	Super Cab	158	56	8' Box	Yes	--
	Crew Cab	156	40	6.75' Box	--	--
	Crew Cab	172	56	8' Box	Yes	--
F-350	Reg. Cab	137	56	8' Box	Yes	--
	Reg. Cab	141	60	--	--	Yes
	Reg. Cab	165	84	--	--	Yes
	Super Cab	142	40	6.75' Box	--	--
	Super Cab	158	56	8' Box	Yes	--
	Super Cab	162	60	--	--	Yes
	Crew Cab	156	40	6.75' Box	--	--
	Crew Cab	172	56	8' Box	Yes	--
	Crew Cab	176	60	--	--	Yes
F-450	Reg. Cab	141	60	--	--	Yes
	Reg. Cab	165	84	--	--	Yes
	Reg. Cab	189	108	--	--	Yes
	Reg. Cab	201	120	--	--	Yes
	Super Cab	162	60	--	--	Yes
	Super Cab	186	84	--	--	Yes
	Crew Cab	172	56	8' Box	--	--
	Crew Cab	176	60	--	--	Yes
	Crew Cab	200	84	--	--	Yes
F-550	Reg. Cab	141	60	--	--	Yes
	Reg. Cab	165	84	--	--	Yes
	Reg. Cab	189	108	--	--	Yes
	Reg. Cab	201	120	--	--	Yes
	Super Cab	162	60	--	--	Yes
	Super Cab	186	84	--	--	Yes
	Crew Cab	176	60	--	--	Yes
	Crew Cab	200	84	--	--	Yes

(1) Box Delete available on 8' box only

2014 SUPER DUTY F-SERIES TRUCKS
Front Spring Selection Chart

F-250 Pickup/Pickup Box Delete

Cab Style/ Drive/WB (in)	Engine/ Transmission	Front Spring Max. Standard (lbs.)	Heavy Duty Front Suspension Package (lbs.)	Camper Package (lbs.)	Snow Plow Package (lbs.)
Regular Cab	6.2L/Automatic	3950	4100	4250	---
4x2 - 137"	6.7L/Automatic	4550	4700	4850	---
Regular Cab	6.2L/Automatic	4400	4800	4800	5600
4x4 - 137"	6.7L/Automatic	5200	5600	5600	6000
SuperCab	6.2L/Automatic	4250	4400	4550	---
4x2 - 142"	6.7L/Automatic	4850	5000	5250	---
SuperCab	6.2L/Automatic	4400	4550	4700	---
4x2 - 158"	6.7L/Automatic	5000	5250	5250	---
SuperCab	6.2L/Automatic	4800	5200	5200	5600
4x4 - 142"	6.7L/Automatic	5200	5600	5600	6000
SuperCab	6.2L/Automatic	4800	5200	5200	6000
4x4 - 158"	6.7L/Automatic	5600	6000	6000	6000
Crew Cab	6.2L/Automatic	4400	4550	4700	---
4x2 - 156"	6.7L/Automatic	5000	5250	5250	---
Crew Cab	6.2L/Automatic	4550	4700	4850	---
4x2 - 172"	6.7L/Automatic	5250	5250	5250	---
Crew Cab	6.2L/Automatic	4800	5200	5200	6000
4x4 - 156"	6.7L/Automatic	5600	6000	6000	6000
Crew Cab	6.2L/Automatic	5200	5600	5600	6000
4x4 - 172"	6.7L/Automatic	5600	6000	6000	6000

Please refer to the Body Builder's Guide for further information regarding front GAWR.

2014 SUPER DUTY F-SERIES TRUCKS
Front Spring Selection Chart

F-350 SRW Pickup/Pickup Box Delete

Standard/Optional GVWR for 17" Wheel & Tire

Cab Style/ Drive/WB (in)	Engine/ Transmission	Front Spring Max. Standard (lbs.)	Heavy Duty Front Suspension Package (lbs.)	Camper Package (lbs.)	Snow Plow Package (lbs.)
Regular Cab	6.2L/Automatic	3950	4100	4250	
4x2 - 137"	6.7L/Automatic	4550	4700	4850	---
Regular Cab	6.2L/Automatic	4400	4800	4800	5600
4x4 - 137"	6.7L/Automatic	5200	5600	5600	6000
SuperCab	6.2L/Automatic	4250	4400	4550	
4x2 - 142"	6.7L/Automatic	4850	5000	5250	---
SuperCab	6.2L/Automatic	4400	4550	4700	---
4x2 - 158"	6.7L/Automatic	5000	5250	5250	---
SuperCab	6.2L/Automatic	4800	5200	5200	6000
4x4 - 142"	6.7L/Automatic	5200	5600	5600	6000
SuperCab	6.2L/Automatic	4800	5200	5200	6000
4x4 - 158"	6.7L/Automatic	5600	6000	6000	6000
Crew Cab	6.2L/Automatic	4400	4550	4700	---
4x2 - 156"	6.7L/Automatic	5000	5250	5250	---
Crew Cab	6.2L/Automatic	4550	4700	4850	---
4x2 - 172"	6.7L/Automatic	5250	5250	5250	---
Crew Cab	6.2L/Automatic	4800	5200	5200	6000
4x4 - 156"	6.7L/Automatic	5600	6000	6000	6000
Crew Cab	6.2L/Automatic	5200	5600	5600	6000
4x4 - 172"	6.7L/Automatic	5600	6000	6000	6000

Please refer to the Body Builder's Guide for further information regarding front GAWR.

Standard/Optional GVWR for 18" Wheel & Tire

Cab Style/ Drive/WB (in)	Engine/ Transmission	Front Spring Max. Standard (lbs.)	Heavy Duty Front Suspension Package (lbs.)	Camper Package (lbs.)	Snow Plow Package (lbs.)
Regular Cab	6.2L/Automatic	3950	4100	4250	---
4x2 - 137"	6.7L/Automatic	4550	4700	4850	---
Regular Cab	6.2L/Automatic	4400	4800	4800	5600
4x4 - 137"	6.7L/Automatic	5200	5600	5600	6000
SuperCab	6.2L/Automatic	4250	4400	4550	---
4x2 - 142"	6.7L/Automatic	4850	5000	5250	---
SuperCab	6.2L/Automatic	4400	4550	4700	---
4x2 - 158"	6.7L/Automatic	5250	5250	5250	---
SuperCab	6.2L/Automatic	4800	5200	5200	6000
4x4 - 142"	6.7L/Automatic	5200	5600	5600	6000
SuperCab	6.2L/Automatic	4800	5200	5200	6000
4x4 - 158"	6.7L/Automatic	5600	6000	6000	6000
Crew Cab	6.2L/Automatic	4400	4550	4700	---
4x2 - 156"	6.7L/Automatic	5000	5250	5250	---
Crew Cab	6.2L/Automatic	4550	4700	4850	---
4x2 - 172"	6.7L/Automatic	5250	5250	5250	---
Crew Cab	6.2L/Automatic	4800	5200	5200	6000
4x4 - 156"	6.7L/Automatic	5600	6000	6000	6000
Crew Cab	6.2L/Automatic	5200	5600	5600	6000
4x4 - 172"	6.7L/Automatic	5600	6000	6000	6000

Please refer to the Body Builder's Guide for further information regarding front GAWR.

2014 SUPER DUTY F-SERIES TRUCKS

Front Spring Selection Chart

F-350 DRW Pickup/Pickup Box Delete[2]

The standard front spring/GAWR[1] on pickup models is computer-selected based on the total front weight of options ordered. Front spring/GAWR upgrades are in increments of 150 lbs. on 4x2 models with spring ratings from **3800 lbs.** to 5250 lbs. and in increments of 400 lbs. on 4x4 models with spring ratings from 4400 lbs. to 6000 lbs. Certain option packages include the following front spring/GAWR upgrades:

Heavy Service Suspension Package	Front springs/GAWR will be selected 1 upgrade higher than standard computer selection
Camper Package	4x2: Front springs/GAWR will be selected 2 upgrades higher than standard computer selection 4x4: Front springs/GAWR will be selected 1 upgrade higher than standard computer selection
Snow Plow Package	Front springs/GAWR is assigned or specifically selected as shown in the chart below.

Front spring/GAWR upgrade is not included if the maximum front spring has been computer-selected as a consequence of options ordered.

Cab Style/ Drive/WB (in)	Engine/ Transmission	Front Spring Max. Standard (lbs.)	Heavy-Service Suspension Package (lbs.)	Camper Package (lbs.)	Snow Plow Package (lbs.)
Regular Cab					
4x2 - 137"	6.2L Automatic	4100	4250	4400	---
	6.7L Automatic	4700	4850	5000	---
Regular Cab					
4x4 - 137"	6.2L Automatic	4800	5200	5200	5600
	6.7L Automatic	5200	5600	5600	6000
SuperCab					
4x2 - 158"	6.2L Automatic	4550	4700	4850	---
	6.7L Automatic	5250	5250	5250	---
SuperCab					
4x4 - 158"	6.2L Automatic	5200	5600	5600	6000
	6.7L Automatic	5600	6000	6000	6000
Crew Cab					
4x2 - 172"	6.2L Automatic	4700	4850	5000	---
	6.7L Automatic	5250	5250	5250	---
Crew Cab					
4x4 - 172"	6.2L Automatic	5200	5600	5600	6000
	6.7L Automatic	5600	6000	6000	6000
	Box Delete	5940	6000	6000	6000

(1) Gross Axle Weight Rating is determined by the rated capacity of the minimum component of the axle system (axle, computer-selected springs, wheels, tires) of a specific vehicle. Front and rear GAWRs will, in all cases, sum to a number equal to or greater than the GVWR for the particular vehicle. Maximum loaded vehicle (including passengers, equipment and payload) cannot exceed the GVW rating or GAWR (front or rear).

(2)The spring selection process also applies to F-250 and F-350 SRW.

Please refer to the Body Builder's Guide for further information regarding front GAWR.

2014 SUPER DUTY F-SERIES TRUCKS

FRONT SPRING SELECTION CHARTS

F-450 Pickup - Standard GVWR

Cab Style/ Drive/WB (in)	Engine	Front Spring Max. Standard (lbs.)	Heavy-Service Suspension Package (lbs.)	Camper Package (lbs.)	Snow Plow Package (lbs.)
Crew Cab 4x4 - 172"	6.7L	6000	6000	6000	6000

2014 SUPER DUTY F-SERIES TRUCKS
FRONT SPRING SELECTION CHARTS

F-350 SRW Chassis Cabs - Standard GVWR

Cab Style/ Drive/WB (in)	Engine	GVWR Standard/ Optional (lbs.)	Front Spring Max. Standard (lbs.)	Heavy-Service Suspension Package (lbs.)	Extra Heavy-Service Suspension Package (lbs.)	Ambulance Prep Package (lbs.)	Fire/Rescue Prep Package[1] (lbs.)	Snow Plow Package (lbs.)
Regular Cab								
4x2 - 141"	6.2L	9800	4100	4250	4400	---	---	---
	6.7L	9800	4700	4850	5000	5250	5250	---
Regular Cab								
4x4 - 141"	6.2L	9800	4800	5200	5600	---	---	5600
	6.7L	9800	5200	5600	6000	6000	6000	6000
SuperCab								
4x2 - 162"	6.2L	9800	4550	4700	4850	---	---	---
	6.7L	9800	5250	5250	5250	5250	5250	---
SuperCab								
4x4 - 162"	6.2L	9800	5200	5600	6000	----	----	6000
	6.7L	9800	5600	6000	6000	6000	6000	6000
Crew Cab								
4x2 - 176"	6.2L	9800	4700	4850	5000	----	----	---
	6.7L	9800	5250	5250	5250	5250	5250	---
Crew Cab								
4x4 - 176"	6.2L	9800	5200	5600	6000	----	----	6000
	6.7L	9800	6000	6000	6000	6000	6000	6000

F-350 SRW Chassis Cabs - 10,000-lb. GVWR

Cab Style/ Drive/WB (in)	Engine	GVWR Standard/ Optional (lbs.)	Front Spring Max. Standard (lbs.)	Heavy-Service Suspension Package (lbs.)	Extra Heavy-Service Suspension Package (lbs.)	Ambulance Prep Package (lbs.)	Fire/Rescue Prep Package[1] (lbs.)	Snow Plow Package (lbs.)
Regular Cab								
4x2 - 141"	6.2L	10,000	4100	4250	4400	---	---	---
	6.7L	10,000	4700	4850	5000	5250	5250	---
Regular Cab								
4x4 - 141"	6.2L	10,000	4800	5200	5600	---	---	5600
	6.7L	10,000	5200	5600	6000	6000	6000	6000
SuperCab								
4x2 - 162"	6.2L	10,000	4550	4700	4850	---	---	---
	6.7L	10,000	5250	5250	5250	5250	5250	---
SuperCab								
4x4 - 162"	6.2L	10,000	5200	5600	6000	----	----	6000
	6.7L	10,000	5600	6000	6000	6000	6000	6000
Crew Cab								
4x2 - 176"	6.2L	10,000	4700	4850	5000	----	----	---
	6.7L	10,000	5250	5250	5250	5250	5250	---
Crew Cab								
4x4 - 176"	6.2L	10,000	5200	5600	6000	----	----	6000
	6.7L	10,000	6000	6000	6000	6000	6000	6000

F-350 SRW Chassis Cabs - Variable GVWR

Cab Style/ Drive/WB (in)	Engine	GVWR (lbs.)	Front Spring Max. Standard (lbs.)	Heavy-Service Suspension Package (lbs.)	Extra Heavy-Service Suspension Package (lbs.)	Ambulance Prep Package (lbs.)	Fire/Rescue Prep Package[1] (lbs.)	Snow Plow Package (lbs.)
Regular Cab								
4x2 - 141"	6.2L	10,200	4100	4250	4400	---	---	---
	6.7L	11,000	4700	4850	5000	5250	5250	---
Regular Cab								
4x4 - 141"	6.2L	10,200	4400	4800	5200	----	----	5600
	6.7L	11,100	5200	5600	6000	6000	6000	6000
SuperCab								
4x2 - 162"	6.2L	10,600	4550	4700	4850	----	----	---
	6.7L	11,500	5250	5250	5250	5250	5250	---
SuperCab								
4x4 - 162"	6.2L	10,600	5200	5600	6000	----	----	6000
	6.7L	11,500	5600	6000	6000	6000	6000	6000
Crew Cab								
4x2 - 176"	6.2L	10,700	4550	4700	4850	----	----	---
	6.7L	11,500	5250	5250	5250	5250	5250	---
Crew Cab								
4x4 - 176"	6.2L	10,700	5200	5600	6000	----	----	6000
	6.7L	11,500	5600	6000	6000	6000	6000	6000

(1) Ford vehicles equipped with the Fire/Rescue Prep Package with Special Emissions – for Diesel Engine (47J) NOT completed as Emergency Vehicles as defined per 40 CFR 86.1803.01 in the Federal Register void the Ford Warranty.

2014 SUPER DUTY F-SERIES TRUCKS

FRONT SPRING SELECTION CHARTS

F-350 DRW Chassis Cabs

Cab Style/ Drive/WB (in)	Engine	GVWR (lbs.)	Front Spring Max. Standard (lbs.)	Heavy-Service Suspension Package (lbs.)	Extra Heavy-Service Suspension Package (lbs.)	Ambulance Prep Package (lbs.)	Fire/Rescue Prep Package[1] (lbs.)	Snow Plow Package (lbs.)
Regular Cab								
4x2 - 141"	6.2L	13,700	4250	4400	4550	----	----	---
	6.7L	14,000	4850	5000	5250	5250	5250	---
Regular Cab								
4x2 - 165"	6.2L	14,000	4850	5000	5250	----	----	---
	6.7L	14,000	5250	5250	5250	5250	5250	---
Regular Cab								
4x4 - 141"	6.2L	14,000	4800	5200	5600	----	----	6000
	6.7L	14,000	5200	5600	6000	6000	6000	6000
Regular Cab								
4x4 - 165"	6.2L	14,000	5200	5600	6000	----	----	6000
	6.7L	14,000	6000	6000	6000	6000	6000	6000
SuperCab								
4x2 - 162"	6.2L	14,000	4700	4850	5000	----	----	---
	6.7L	14,000	5250	5250	5250	5250	5250	---
SuperCab								
4x4 - 162"	6.2L	14,000	5200	5600	6000	----	----	6000
	6.7L	14,000	6000	6000	6000	6000	6000	6000
Crew Cab								
4x2 - 176"	6.2L	14,000	4850	5000	5250	----	----	---
	6.7L	14,000	5250	5250	5250	5250	5250	---
Crew Cab								
4x4 - 176"	6.2L	14,000	5200	5600	6000	----	----	6000
	6.7L	14,000	6000	6000	6000	6000	6000	6000

(1) Ford vehicles equipped with the Fire/Rescue Prep Package with Special Emissions – for Diesel Engine (47J) NOT completed as Emergency Vehicles as defined per 40 CFR 86.1803.01 in the Federal Register void the Ford Warranty.

2014 SUPER DUTY F-SERIES TRUCKS
FRONT SPRING SELECTION CHARTS

F-450 Chassis Cabs - Standard 16,500 lb. & Optional 16,000/15,000 lb. GVWR

Cab Style/ Drive/WB (in)	Engine	GVWR Standard/ Optional/ Optional (lbs.)	Front Spring Max. Standard (lbs.)	Heavy-Service Suspension Package (lbs.)	Extra Heavy-Service Suspension Package (lbs.)	Ambulance Prep Package (lbs.)	Fire/Rescue Prep Package[(1)] (lbs.)	Snow Plow Package (lbs.)
Regular Cab	6.8L	16,500/16,000/ 15,000	4800	5200	5600	----	----	6500
4x2 - 141"	6.7L	16,500/16,000/ 15,000	5600	6000	6500	7000	7000	7000
Regular Cab	6.8L	16,500/16,000/ 15,000	5200	5600	6000	----	----	6500
4x2 - 165"	6.7L	16,500/16,000/ 15,000	6000	6500	7000	7000	7000	7000
Regular Cab	6.8L	16,500/16,000/ 15,000	5600	6000	6500	----	----	6500
4x2 - 189"	6.7L	16,500/16,000/ 15,000	6500	7000	7000	7000	7000	7000
Regular Cab	6.8L	16,500/16,000/ 15,000	6000/6000/ 5600	6500/6500/ 6000	7000/7000/ 6500	----	----	6500
4x2 - 201"	6.7L	16,500/16,000/ 15,000	6500	7000	7000	7000	7000	7000
Regular Cab	6.8L	16,500/16,000/ 15,000	4800	5200	5600	----	----	6500
4x4 - 141"	6.7L	16,500/16,000/ 15,000	5600	6000	6500	7000	7000	7000
Regular Cab	6.8L	16,500/16,000/ 15,000	5600	6000	6500	----	----	6500
4x4 - 165"	6.7L	16,500/16,000/ 15,000	6500/6500/6000	7000/7000/6500	7000	7000	7000	7000
Regular Cab	6.8L	16,500/16,000/ 15,000	6000	6500	7000	----	----	7000
4x4 - 189"	6.7L	16,500/16,000/ 15,000	7000/7000/6500	7000	7000	7000	7000	7000
Regular Cab	6.8L	16,500/16,000/ 15,000	6000	6500	7000	----	----	7000
4x4 - 201"	6.7L	16,500/16,000/ 15,000	7000/7000/ 6500	7000	7000	7000	7000	7000
SuperCab	6.8L	16,500/16,000/ 15,000	5200	5600	6000	----	----	6500
4x2 - 162"	6.7L	16,500/16,000/ 15,000	6000/6000/ 5600	6500/ 6500/ 6000	7000/7000/ 6500	7000	7000	7000
SuperCab	6.8L	16,500/16,000/ 15,000	5600	6000	6500	----	----	6500
4x2 - 186"	6.7L	16,500/16,000/ 15,000	6500/6500/ 6000	7000/7000/ 6500	7000	7000	7000	7000
SuperCab	6.8L	16,500/16,000/ 15,000	5600/5600/5200	6000/5600/5600	6500/6000/6000	----	----	7000
4x4 - 162"	6.7L	16,500/16,000/ 15,000	6000	6500	7000	7000	7000	7000
SuperCab	6.8L	16,500/16,000/ 15,000	6000/6000/ 5600	6500/6500/ 6000	7000/7000/ 6500	----	----	7000
4x4 - 186"	6.7L	16,500/16,000/ 15,000	6500	7000	7000	7000	7000	7000
Crew Cab	6.8L	16,500/16,000/ 15,000	5200	5600	6000	----	----	6500
4x2 - 176"	6.7L	16,500/16,000/ 15,000	6000	6500	7000	7000	7000	7000
Crew Cab	6.8L	16,500/16,000/ 15,000	5600	6000	6500	----	----	6500
4x2 - 200"	6.7L	16,500/16,000/ 15,000	6500	7000	7000	7000	7000	7000
Crew Cab	6.8L	16,500/16,000/ 15,000	5600	6000	6500	----	----	7000
4x4 - 176"	6.7L	16,500/16,000/ 15,000	6500/6500/6000	7000/7000/6500	7000	7000	7000	7000
Crew Cab	6.8L	16,500/16,000/ 15,000	6000	6500	7000	----	----	7000
4x4 - 200"	6.7L	16,500/16,000/ 15,000	7000/7000/6500	7000	7000	7000	7000	7000

(1) Ford vehicles equipped with the Fire/Rescue Prep Package with Special Emissions – for Diesel Engine (47J) NOT completed as Emergency Vehicles as defined per 40 CFR 86.1803.01 in the Federal Register void the Ford Warranty.

2014 SUPER DUTY F-SERIES TRUCKS
FRONT SPRING SELECTION CHARTS

F-550 Chassis Cabs - Standard/Optional GVWR

Cab Style/ Drive/WB (in)	Engine	GVWR Standard/ Optional/ Optional (lbs.)	Front Spring Max. Standard (lbs.)	Heavy-Service Suspension Package (lbs.)	Extra Heavy-Service Suspension Package (lbs.)	Ambulance Prep Package (lbs.)	Fire/Rescue Prep Package[(1)] (lbs.)	Snow Plow Package (lbs.)
Regular Cab	6.8L	18,000/17,500/ 19,000	4800/4800/ 6000	5200/5200/ 6500	5600/5600/ 7000	----	----	6500
4x2 - 141"	6.7L	18,000/17,500/ 19,500	5600	6000	6500	7000	7000	7000
Regular Cab	6.8L	18,000/17,500/ 19,500	5600	6000	6500	----	----	6500
4x2 - 165"	6.7L	18,000/17,500/ 19,500	6000/6000/ 6500	6500/6500/ 7000	7000	7000	7000	7000
Regular Cab	6.8L	18,000/17,500/ 19,500	6000/6000/ 6500	6500	7000	----	----	6500
4x2 - 189"	6.7L	18,000/17,500/ 19,500	7000/6500/ 7000	7000	7000	7000	7000	7000
Regular Cab	6.8L	18,000/17,500/ 19,500	6000/6000/ 6500	6500	7000	----	----	6500
4x2 - 201"	6.7L	18,000/17,500/ 19,500	7000/6500/ 7000	7000	7000	7000	7000	7000
Regular Cab	6.8L	18,000/17,500/ 19,000	5200/5200/ 6000	5600/5600/ 6500	6000/6000/ 7000	----	----	6500/6500/7000
4x4 - 141"	6.7L	18,000/17,500/ 19,500	6000/5600/6000	6500/6000/6500	7000/6500/7000	7000	7000	7000
Regular Cab	6.8L	18,000/17,500/ 19,500	5600/5600/ 6000	6000/6000/ 6500	6500/6500/ 7000	----	----	6500/6500/7000
4x4 - 165"	6.7L	18,000/17,500/ 19,500	6500	7000	7000	7000	7000	7000
Regular Cab	6.8L	18,000/17,500/ 19,500	6500/6000/ 6500	7000/6500/ 7000	7000	----	----	7000
4x4 - 189"	6.7L	18,000/17,500/ 19,500	7000	7000	7000	7000	7000	7000
Regular Cab	6.8L	18,000/17,500/ 19,500	6500	7000	7000	----	----	7000
4x4 - 201"	6.7L	18,000/17,500/ 19,500	7000	7000	7000	7000	7000	7000
SuperCab	6.8L	18,000/17,500/ 19,500	5200	5600	6000	----	----	6500
4x2 - 162"	6.7L	18,000/17,500/ 19,500	6000	6500	7000	7000	7000	7000
SuperCab	6.8L	18,000/17,500/ 19,500	5600/5600/ 6000	6000/6000/ 6500	6500/6500/ 7000	----	----	6500
4x2 - 186"	6.7L	18,000/17,500/ 19,500	6500	7000	7000	7000	7000	7000
SuperCab	6.8L	18,000/17,500/ 19,500	5600	6000	6500	----	----	7000
4x4 - 162"	6.7L	18,000/17,500/ 19,500	6500	7000	7000	7000	7000	7000
SuperCab	6.8L	18,000/17,500/ 19,500	6000	6500	7000	----	----	7000
4x4 - 186"	6.7L	18,000/17,500/ 19,500	7000/6500/ 7000	7000	7000	7000	7000	7000
Crew Cab	6.8L	18,000/17,500/ 19,500	5200	5600	6000	----	----	6500
4x2 - 176"	6.7L	18,000/17,500/ 19,500	6000	6500	7000	7000	7000	7000
Crew Cab	6.8L	18,000/17,500/ 19,500	5600/5600/ 6000	6000/6000/ 6500	6500/6500/ 7000	----	----	6500/6500/ 7000
4x2 - 200"	6.7L	18,000/17,500/ 19,500	6500	7000/7000/ 6500	7000	7000	7000	7000
Crew Cab	6.8L	18,000/17,500/ 19,500	5600	6000	6500	----	----	7000
4x4 - 176"	6.7L	18,000/17,500/ 19,500	6500	7000	7000	7000	7000	7000
Crew Cab	6.8L	18,000/17,500/ 19,500	6000	6500	7000	**----**	**----**	7000
4x4 - 200"	6.7L	18,000/17,500/ 19,500	7000	7000	7000	7000	7000	7000

(1) Ford vehicles equipped with the Fire/Rescue Prep Package with Special Emissions – for Diesel Engine (47J) NOT completed as Emergency Vehicles as defined per 40 CFR 86.1803.01 in the Federal Register void the Ford Warranty.